

BARCALDINE REGIONAL COUNCIL

DIGITALLY STAMPED
APPROVED DOCUMENT

Development Permit – Material Change of Use for:
"Community Oriented Activity" – "Public Utility"
– Waste Management Facility

referred to in and subject to the conditions in Council's
Decision Notice

Approval Date: 13 November 2017
Application Number: DA421617

Appendix M

Report: “Hydrogeological Investigation Report”



71 Ash Street
PO Box 191
BARCALDINE QLD 4725

BARCALDINE REGIONAL COUNCIL WASTE MANAGEMENT FACILITY

HYDROGEOLOGICAL INVESTIGATION REPORT

MARCH 2016



Version History

Date	Name	Position	Action required (Review/Endorse/Approve)
02/03/2017	W. Green	Environmental Engineer	Review
03/03/2017	S. Bourne	Senior Engineer	Approved

Prepared by William Green
Title Environmental Engineer, George Bourne & Associates, Barcaldine QLD
Location 67 Elm Street, Barcaldine, QLD 4725
Version date 02/03/2017
Status Report
File/Doc No. 140010

Contact for enquiries and proposed changes

If you have any questions regarding this document or if you have a suggestion for improvements, please contact:



Project Manager Simon Bourne **RPEQ:** 1513

Phone 07 4651 2177

TABLE OF CONTENTS

1. Scope.....	1
2. Introduction.....	1
3. Investigation Methodologies.....	2
3.1 Test Hole Drilling and Sampling	2
3.2 Landfill Cell Base Sampling.....	2
4. Results.....	2
4.1 Test Hole Drilling and Sampling	2
4.2 Landfill Cell Base Sampling.....	4
5. Discussion.....	6
5.1 Test Hole Drilling and Sampling	6
5.2 Landfill Cell Base Sampling.....	6
6. Conclusions	7

Figure 1 Location Map - Barcaldine Waste Management Facility 1

Figure 2 Summary of Drill Log Strata Descriptions..... 3

Table 1 Test Hole Locations and Depths..... 2

Table 2 Landfill Cell Base Sampling Locations and Depths..... 2

Table 3 Materials Testing Core Sample Summary 3

Table 4 Summary of Soil Testing Results - Material Underlying Landfill Cell..... 5

APPENDICES

Appendix 1A Test Hole Drill Log Forms

Appendix 1B Test Hole Core Samples Quality of Materials Report


Appendix 2A Landfill Cell Base Moisture Density & Atterberg Limit Reports

Appendix 2B Landfill Cell Base Permeability Reports

1. Scope

This report has been developed to present the findings of a hydrogeological investigation undertaken to identify the suitability of the underlying geology and ground water for the proposed development of the Barcaldine Waste Management Facility. Located on Yellowjack Drive approximately 4km south west of the township of Barcaldine.

Figure 1 Location Map - Barcaldine Waste Management Facility



2. Introduction

An investigation has been conducted to determine the geotechnical properties of the underlying geology and groundwater levels at the site. The investigation was done in two stages:

- i) Test Hole Drilling and Sampling: The first stage of the investigation included the drilling of test holes to determine if a shallow water table was present and whether a considerable level of separation could be achieved between the proposed landfill cell base (proposed depth 7m) and the water table. Another aspect of this initial investigation was to determine the characteristics of the underlying geology of the site and take core samples for analysis below the proposed landfill cell.
- ii) Landfill Cell Base Sampling: A second round of material testing investigations were undertaken to analyse the characteristics of the insitu material immediately below the base of the landfill cell. These tests were conducted primarily to determine if the insitu material at the base of the landfill cell possessed hydraulic conductivity values capable of restricting the leaching of contaminants to the groundwater system to avoid contamination. These samples taken immediately below the landfill cell were also tested for Atterberg Limits and Moisture Density Relationships.

3. Investigation Methodologies

3.1 Test Hole Drilling and Sampling

Four test holes were drilled at 2 locations; a southern and a northern location. The southern location is mid-way along the southern boundary of the facility and the northern location is adjacent to the southern test hole location on the northern boundary. Table 1 below provides a summary of the test hole locations and depths.

Table 1 Test Hole Locations and Depths

Test Hole ID		Location - Lat	Location - Lon	Depth (m)
001	Southern Site	-23.587602	145.265333	04.0
002		-23.587584	145.265333	18.0
003	Northern Site	-23.585134	145.265131	11.2
004		-23.585116	145.265131	04.0

Soil samples were taken at the lower depths of Test Hole 002 to determine the soil properties of the material underlying the proposed landfill cell. The core samples were taken at 8-12m, 14-15m and 16-17m depths, these samples were tested for Particle Size Distribution and Atterberg Limits.

3.2 Landfill Cell Base Sampling

Following the initial test hole sampling, materials tests were conducted immediately below the landfill cell base in 4 locations at depths of 0.5m and 1.5m, approximately 7.5 and 9 m below ground level. For each sampling point Atterberg Limits, Moisture Density Relationships and Permeability Testing was conducted. A summary of testing points and locations are provided in table 2 below.

Table 2 Landfill Cell Base Sampling Locations and Depths

Sample ID	Location - Lat	Location - Lon	Depth (m)
WS17-8	-23.585538	145.266160	0.5
WS17-9	-23.585538	145.266160	1.5
WS17-10	-23.585576	145.266286	0.5
WS17-11	-23.585576	145.266286	1.5
WS17-12	-23.585315	145.266169	0.5
WS17-13	-23.585315	145.266169	1.5
WS17-14	-23.585330	145.266359	0.5
WS17-15	-23.585330	145.266359	1.5

4. Results

4.1 Test Hole Drilling and Sampling

Groundwater


As detailed in table 1 four test holes were drilled in two locations, with a shallow and a deeper test hole drilled at either location. On the southern drilling site Test Hole 002 was drilled to a maximum depth of 18m and at the northern site a maximum depth of 11.2m was reached at Test Hole 003. The drilling logs identified that ground water was not reached at these depths. Regular inspections since the

time of drilling have taken place to determine if fluctuations in water table depths occur and can be detected at these depths.

Underlying Strata

As the test hole sites were drilled a description was made for the different strata types encountered during drilling in the Drilling Log Forms. The underlying strata found at the drilling locations showed a high level of consistency between drilling locations in the strata type and horizon depths. A summary of the underlying strata based on the Drilling Log Forms is provided below in figure 2. Drill Log Forms are attached in Appendix 1a.

Figure 2 Summary of Drill Log Strata Descriptions



Materials Testing Core Samples

Core samples were taken from Test Hole 002 at 8-12m, 14-15m and 16-17m depths. These samples were taken to determine the properties of the materials underlying the proposed landfill cell. The samples were tested for Particle Size Distribution and Atterberg Limits. A complete set of core sample Quality of Materials Reports are attached in appendix 1b. A summary of test results are provided below in table 3.

Table 3 Materials Testing Core Sample Summary

Sample	Liquid Limit %	Plastic Index %	Linear Shrinkage %
Location 1 8-12m Depth	59	39	17
Location 2 14-15m Depth	71	24	19
Location 3 16-17m Depth	71	48	19.5

4.2 Landfill Cell Base Sampling

Following the initial test hole investigation, further testing was conducted on the materials directly underlying the landfill cell. Analysis of the hydraulic conductivity and physical characteristics of the material was conducted, to determine the capacity of the material to restrict the leaching of contaminants beyond the vicinity of the landfill cell base. In order to determine the suitability of the insitu material underlying the landfill cell a range of tests were conducted, including; Moisture Density Relationship testing, Atterberg Limits and Permeability testing. A summary of these results are provided in table 4 on the following page.

Table 4 Summary of Soil Testing Results - Material Underlying Landfill Cell

Location	Sample Number	Depth (m)	Liquid Limit (%)	Plasticity index (%)	Linear shrinkage (%)	maximum dry density (t/m ³)	Optimum Moisture Content (%)	Coefficient of Permeability m/s	Coefficient of Permeability mm/yr
1	WS17-8	0.5	24.6	19.4	2.4	1.8664	12.4	3E-009	94.67
1	WS17-9	1.5	27	19.2	3.6	1.92	11.9	9E-010	28.40
2	WS17-10	0.5	25.8	21.2	3.4	1.866	12.3	9E-010	28.40
2	WS17-11	1.5	27.2	21.8	3.2	1.904	11.7	6E-009	189.35
3	WS17-12	0.5	22	19.2	2.8	1.915	11.3	2E-009	63.11
3	WS17-13	1.5	25.4	19	2.6	1.882	12.8	8E-010	25.25
4	WS17-14	0.5	20.4	7.4	3.8	1.891	11.7	8E-010	25.25
4	WS17-15	1.5	21.6	9.2	3.2	1.88	12	2E-009	63.11

5. Discussion

5.1 Test Hole Drilling and Sampling

One objective for the drilling of test holes was to determine if a suitable distance of separation could be achieved between the proposed landfill cell base and the uppermost groundwater aquifer. The drilling of test holes at varied depths from 4m to 18m did not locate a water aquifer. Since the test holes were drilled they have been inspected regularly, particularly after large rainfall events to determine if water persists at these depths, water has not been identified at these locations.

The strata descriptions from the 4 test hole locations indicate a uniform strata formation across the site. As depicted in Section 4.1 figure 2 the upper strata layer is a sandy layer associated with the naturally occurring sandy loam plains encountered in the district. This sandy material then transitions into what is described as a silty material; then into a more solidified material described in the drilling logs as a sandstone type material. Underlying this sandstone material at approximately 7m depth the material has been described as a clay material.

The Quality of Material Reports for the core samples tested from test hole 002 provide information relating to the type of material underlying the landfill cells. The Quality of Materials Reports are provided in appendix 1b. These reports indicate that the material found between 8 and 16 metres is fine grained material with more than 75% of materials passing through a .075mm sieve and 90% or greater for the samples taken at lower depths from locations 2 and 3. Plasticity index results greater than 30 are considered to be highly plastic and have a high clay content. The materials test results therefore identify all of the core samples from Test Hole 002 as highly plastic. The linear shrinkage results from the material quality reports also indicate that a high clay content is present with linear shrinkage values ranging from 17 to 19.5%. The Quality of Materials Reports from core samples taken from Test Hole 002 identify a relatively deep layer of fine grained clay material is present below the proposed landfill cell, ranging from approximately 8m to 17m or greater depths. These materials may not be ideal for lining materials due to the shrink swell characteristics identified, however when occurring at significant depths such as these, large fluctuations in moisture conditioning and subsequent desiccation cracking is unlikely. The underlying clay strata below the landfill cell provides a favourable medium in preference to courser permeable material or solidified material prone to fracture.

5.2 Landfill Cell Base Sampling

Following the initial test hole studies another round of material suitability investigations were undertaken. These samples were taken from within the perimeter of the proposed landfill cell at depths of 0.5 and 1.5m below the proposed landfill cell base (approximately 7.5 and 9m below ground level), materials were tested for Atterberg Limits, Moisture Density and Permeability.

The characteristics of the insitu materials underlying the base of the cell have been characterised as clayey sand material for all of the samples taken. The Atterberg Limit results for these samples demonstrate slight to medium plasticity characteristics, with plasticity index scores ranging from 7.4-21.8% and liquid limits ranging from 20.4-27.2%. In correlation with plasticity values linear

shrinkage values were relatively low with scores ranging from 2.4-3.8%. Relatively low plasticity values and shrink swell characteristics for materials utilised as landfill cell liners are favourable characteristics as materials with a low plasticity index are less susceptible to desiccation cracking compared to clays with a high plasticity and shrink swell characteristics.

Permeability values for the soils tested from the base of the landfill cell at depths of 0.5 and 1.5m indicate that these materials possess low hydraulic conductivity values with permeability values ranging from 25.25-189.5mm/yr. These results indicate the insitu materials forming the underlying strata of the landfill cell would have the capacity to greatly restrict the flow of leachate material from the landfill cell avoiding the contamination of underlying groundwater systems.

6. Conclusions

Results obtained from both the initial test hole study and the soil testing from the landfill cell location indicate that the geological strata of the site has the capacity to restrict the leaching of potential contaminants from causing pollution to the groundwater system. This investigation has also identified the absence of a shallow water table at this site.

The drilling of test holes at two locations with maximum drilling depths of 18 and 11m at the Southern and Northern sites respectfully was conducted without the detection of groundwater. Indicating a significant separation distance between the landfill cell base and the uppermost groundwater aquifer. Inspections following the drilling of the bores has failed to identify any water at these depths even following substantial rainfall events.

The test hole strata descriptions identify a uniform strata formation across the site. Materials testing from the deepest of the test holes (Test Hole 002) provides Atterberg limits and Particle Size Distributions for core samples between the depths of 8-17m. The materials testing values for the core samples demonstrates fine grained material is present at these depths; plasticity and linear shrinkage values indicate a high level of plasticity consistent with clay material. These clay materials prevailing to significant depths below the landfill cell identify the absence of porous or fractured material.

Material testing below the landfill cell sampled at 0.5 and 1.5 depth provided values for Atterberg Limits, Moisture Density and Permeability. This material was characterised as a Sandy Clay. The Atterberg Limit values identify these soils to be slightly – medium plastic, in correlation with the plasticity values linear shrinkage values were low and ranged from 2.4-3.8%. These plasticity values identify a low susceptibility to desiccation cracking, a desirable characteristic for landfill cell base material. Permeability results indicate low permeability values for these soils ranging from 6×10^{-9} – 8×10^{-10} , although these results show some variation they indicate the capacity to greatly restrict the leaching of contaminants from the landfill cell.

This investigation has identified the insitu materials at this site are conducive to the implementation of a landfill site. It has been determined there is a significant distance of separation between the landfill cell base and the uppermost groundwater aquifer; the material immediately below the base of the landfill cell has low permeability and plasticity values providing a natural leachate barrier with a low susceptibility to desiccation cracking; and the material underlying the cell base is a fine grained clay material persisting to a significant depth below the landfill cell.

Appendix 1a

Test Hole Drill Log Forms

Drill log form

Authorisation details

Registered number _____

Development permit number _____

Queensland
Government

1037752

SECTION A—LOCATION DETAILS

Name of landholder Buncalbin Regional Council Phone No. 46575 600
 Postal address P.O. Box 191 Buncalbin Postcode 47225
 Real property address New Bilkish Tys Buncalbin Postcode 47225 Plan S 1223525 or Bore location GPS. Latitude 23°35'55.5" Longitude 145°05'20.5" Datum E

Real property description Lot 1 Easting Northing Zone —

SECTION D—HOLE SIZE

Diameter (mm)	Location (metres) From To	Location (metres) From To	Location (metres) From To
121	0	1.5	
120	1.5	1.8	

SECTION E—CASING DETAILS

Type (PVC, steel etc)	Size O.D. (mm)	Wall thickness (mm)	Location (metres) From To
PVC	60	5.1	0
Steel	114	4	10.5

SECTION F—CENTRALISERS TYPE

Type	Location (metres) From To
	7.4
	7.4

SECTION G—PERFORATIONS/ SLOTS/ SCREENS

Type	Size O.D. (mm)	Aperture (mm)	Location (metres) From To
Slots	60	0-4	5.1

SECTION H—CEMENTING/ GRAVEL PACK/ ANNULLAR FILL DETAILS

Type & material size	Hole diameter (mm)	Casing diameter (mm O.D.)	Location (metres) From To
Concreat	171	114	0
Grout	170	60	1.5
Bentonite	120	60	4.5
Gravel	120	60	5

SECTION I—BORE PURPOSE

Domestic	Stock	Irrigation	Commercial Other (please specify) <u>Monitoring</u>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

SECTION J—PARTICULARS OF STRATA

From (metres)	To (metres)	Strata description (use more than one line if required)	Water bed thrust(*)
0	3.1	<u>yellow sand</u>	<u>Conductivity(EC)</u>
3.7	4.8	<u>silt stone</u>	<u>pH</u>

SECTION K—WATER BEARING BEDS

Depth struck (metres)	Water rose to (metres)	Supply (litres/second)	Quality (e.g. potable, brackish, salty)
			<u>dry</u>

SECTION L—SUB ARTESIAN BORE ON COMPLETION

Depth to standing water level from ground level	Depth to pump suction or bottom of drill stem (metres)

SECTION M—ARTESIAN BORE ON COMPLETION

Pressure (kPa)	Duration of test (hours)	Drawdown level from surface (metres)

White — forward to the Department of Environment and Resource Management. Pink — provide to landholder. Blue — Driller to retain.

The information being collected in this form will be used by this department for the purpose of processing your drill log form to record your water bore drilling activity under the authority of section 313 of the Water Act 2000. Your personal details will be accessed only by authorised officers within this department and will not be disclosed to any other third party without your consent except where required by law. The information collected will be retained as required by the Public Records Act 2002 (Qld) and may be stored in a departmental database. For more information on the department's privacy commitment, please visit www.derm.qld.gov.au/privacy.

03/09/2010 B28874
 SECTION N—REMARKS
 I hereby certify that the bore is drilled and constructed according to the conditions of my driller's licence and the information provided in sections A to E and section H above is true, accurate and complete to the best of my knowledge and belief.
 Driller Brett Wehl Driller's Licence No. 3079
 Trainee Driller _____
 Signature of Driller Brett Wehl Date 24/8/2014
 Contractor Brett Wehl

Drill log form



1037753

Authorisation details

Registered number _____

Development permit number _____

Queensland
Government

SECTION A—LOCATION DETAILS

Name of landholder Bundaberg Regional Council

Phone No. 46515600

Postcode 4725

Postcode 4725

Real property address PO Box 191 Bundaberg

Real property description New Bullock Twp Baseline

Lot SP223525

Plan SP223525

or Bore location GPS. Latitude 23°35'10.7S

Longitude 145°15'9.8E

Datum WGS84

Easting -----

Northing -----

Zone -----

Works reference number Q03

SECTION B—BORE COMPLETION DETAILS

Date commenced 22/8/2014

Date completed 23/8/2014

SECTION C—DRILLING METHOD

Rotary mud

Cable tool

Rotary air

Auger

Other _____

03/09/2010 #28874

SECTION D—HOLE SIZE

Diameter

(mm)

Location (metres)

To

From

0

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

SECTION E—CASING DETAILS

Type

(PVC, steel etc)

Size O.D.

(mm)

Wall thickness

(mm)

Location (metres)

To

From

0

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

SECTION F—CENTRALISERS TYPE

Type

Location (metres)

To

From

0

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

SECTION G—PERFORATIONS/ SLOTS/ SCREENS

Type

Size O.D.

(mm)

Aperture

(mm)

Location (metres)

To

From

0

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

SECTION H—CEMENTING/ GRAVEL PACK/ ANNULAR FILL DETAILS

Type

hole diameter (mm)

casing diameter (mm O.D.)

From

To

0

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

1.2

Drill log form



Queensland
Government

1037754

Development permit number

Works reference number **004**

Authorisation details

SECTION A—LOCATION DETAILS

Name of landholder **Banora Regional Council**
Postal address **Po Box 191 Banora Line**
Real property address **New Bulloch Tce Banora Line**
Real property description Lot **1** Plan **SD233525** or Bore location GPS. Latitude **25°35'10.8"S** Longitude **145°13'9.0"E**

SECTION D—HOLE SIZE

Diameter (mm)	Location (metres) From To	To	Stock	Irrigation	Commercial	Other (please specify) Monitoring
171	0	1.5				
120	1.5	4				

SECTION E—CASING DETAILS

Type (PVC, steel etc)	Size O.D. (mm)	Wall thickness (mm)	Location (metres) From To	From To	Conductivity(EC) thus(*)	pH
PVC	60	5.1	0	3.53	2.5	
Steel	114	4	+0.5	1		

SECTION F—CENTRALISERS TYPE

Type	Location (metres) From To	Drawdown level from surface (metres)

SECTION G—PERFORATIONS/ SLOTS/ SCREENS

Type	Size O.D. (mm)	Aperture (mm)	Location (metres) From To	Free flow (litres/second)	Temperature (°C)
Slots	60	0.4	2.03	3.53	

SECTION H—CEMENTING/ GRAVEL PACK/ ANNULAR FILL DETAILS

Type & material size	Hole diameter (mm)	Casing diameter (mm O.D.)	Location (metres) From To	Driller's Licence No.
concrete	170	114	0	1.5
gravel	120	60	1.5	2
gravel	120	60	2	3.53
bitonite	120	60	3.53	4

SECTION I—BORE PURPOSE

Domestic	Stock	Industrial	Date commenced 5/8/2014	Date completed 23/8/2014
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>		

SECTION J—PARTICULARS OF STRATA

From (metres)	To (metres)	Strata description (use more than one line if required)	Water bed thus(*)	Conductivity(EC)	pH
0	2.5	yellow sand			

SECTION K—WATER BEARING BEDS

Depth struck (metres)	Water rose to (metres)	Supply (litres/second)	Quality (e.g. potable, brackish, salty)

SECTION L—SUB ARTESIAN BORE ON COMPLETION

Depth to standing water level from ground level (metres)	Depth to pump suction or bottom of drill stem (metres)	Type of test used	Est. supply (litres/second)	Duration of test (hours)	Drawdown level from surface (metres)
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

SECTION M—ARTESIAN BORE ON COMPLETION

Pressure (kPa)	Free flow (litres/second)	Temperature (°C)

SECTION N—REMARKS

I hereby certify that the bore is drilled and constructed according to the conditions of my driller's licence and the information provided in sections A to E and section H above is true, accurate and complete to the best of my knowledge and belief.

Brett Wehl Driller's Licence No. **3079**
Trainee Driller _____
Driller's Licence No. _____
Signature of Driller **Brett Wehl**
Contractor **Brett Wehl**

Department of Environment and Resource Management

The information being collected in this form will be used by this department for the purpose of processing your water bore drilling activity under the authority of section 333 of the Water Act 2000. Your personal details will be accessed only by authorised officers within this department and will not be disclosed to any other third party without your consent except where required by law. The information collected will be retained as required by the Public Records Act 2002 (Qld) and may be stored in a departmental database. For more information on the department's privacy commitment, please visit www.derm.qld.gov.au/privacy.

White — forward to the Department of Environment and Resource Management. Pink — provide to landholder. Blue — Drill to retain.

DRR74A
2000/2001
Form 3/2001

Appendix 1b

**Test Hole Core Samples Quality of Materials
Report**



Cardno Construction Sciences
ABN: 74 126 606 735
Address:
37 Camel Street,
Grafton QLD 4614


Laboratory: Townsville Laboratory
Phone: 0747288023 Fax: 0747288024
Email: michael.midgley@cardno.com.au

QUALITY OF MATERIALS REPORT

Client:	Barcaldine Regional Council	Report Number:	10599/R/8306-1
Client Address:	Regional Council, PO Box 191, Barcaldine	Project Number:	10599/P/337
Project:	General Testing	Lot Number:	New Refuse Tip- Development
Location:	Barcaldine	Internal Test Request:	10599/T/3454
Component:	Quality Compliance	Client Reference/s:	203627
Area Description:	Drilled Clay Samples	Report Date / Page:	11/09/2014 Page 1 of 3

Test Procedures	AS1289.3.6.1, AS1289.3.1.2, AS1289.3.2.1, AS1289.3.4.1, AS1289.2.1.1, AS 1289.3.3.1
Sample Number	10599/S/19331
Sampling Method	Tested as Received
Date Sampled	8/09/2014
Sampled By	Client Sampled
Date Tested	8/09/2014
Att. Drying Method	Oven Dried
Atterberg Preparation	Dry Sieved

AS Sieve (mm)	Specification Minimum	Percent Passing (%)	Specification Maximum
19.0		100	
16.0		100	
13.2		100	
9.5		100	
6.7		100	
4.75		100	
2.36		97	
1.18		95	
0.600		93	
0.425		91	
0.300		86	
0.150		80	
0.075		77	



Test Result	Specification Minimum	Result	Specification Maximum	Test Result	Specification Minimum	Result	Specification Maximum
Liquid Limit (%)		59		0.075/0.425 Fines Ratio		0.85	
Plastic Limit (%)		20		PI x 0.425 Ratio (%)		3549.0	
Plastic Index (%)		39		LS x 0.425 Ratio (%)		1547.0	
Linear Shrinkage (%)		17.0		Linear Shrinkage Defects	curl		

Remarks

<p>NATA</p> <p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 10599</p>	<p><i>Nathan Lyne</i></p> <p>Approved Signatory: Nathan Lyne Form ID: W85Rep Rev 1</p>
--	--




Cardno Construction Sciences
ABN: 74 128 806 735
Address:
37 Carmel Street,
Gardenvale QLD 4814

Laboratory: Townsville Laboratory
Phone: 0747288023 Fax: 0747288024
Email: michael.middleby@cardno.com.au

QUALITY OF MATERIALS REPORT

Client:	Barcaldine Regional Council	Report Number:	10599/R/8306-1
Client Address:	Regional Council, PO Box 191, Barcaldine	Project Number:	10599/P/337
Project:	General Testing	Lot Number:	New Refuse Tip- Development
Location:	Barcaldine	Internal Test Request:	10599/T/3454
Component:	Quality Compliance	Client Reference/s:	203627
Area Description:	Drilled Clay Samples	Report Date / Page:	11/09/2014
			Page 2 of 3

Test Procedures	AS1289.3.6.1, AS1289.3.1.2, AS1289.3.2.1, AS1289.3.4.1, AS1289.2.1.1, AS 1289.3.3.1		
Sample Number	10599/S19332	Location	14-15m
Sampling Method	Tested as Received		
Date Sampled	8/09/2014		
Sampled By	Client Sampled		
Date Tested	8/09/2014	Material Source	CLIENT
Att. Drying Method	Oven Dried	Material Type	Clay Fill
Atterberg Preparation	Dry Sieved	Material Description	-



Test Result	Specification Minimum	Result	Specification Maximum	Test Result	Specification Minimum	Result	Specification Maximum
Liquid Limit (%)		71		0.075/0.425 Fines Ratio		0.94	
Plastic Limit (%)		24		PI x 0.425 Ratio (%)		4606.0	
Plastic Index (%)		47		LS x 0.425 Ratio (%)		1862.0	
Linear Shrinkage (%)		19.0		Linear Shrinkage Defects	curl		

Remarks



The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards.
Accredited for compliance with ISO/IEC 17025

Accreditation Number: 1986
Corporate Site Number: 10599

Myne

Approved Signatory: Nathan Lyne


Form ID: W85Rep Rev 1

QUALITY OF MATERIALS REPORT

Client:	Barcaldine Regional Council	Report Number:	10599/R/8306-1
Client Address:	Regional Council, PO Box 191, Barcaldine	Project Number:	10599/P/337
Project:	General Testing	Lot Number:	New Refuse Tip- Development
Location:	Barcaldine	Internal Test Request:	10599/T/3454
Component:	Quality Compliance	Client Reference/s:	203627
Area Description:	Drilled Clay Samples	Report Date / Page:	11/09/2014 Page 3 of 3

Test Procedures	AS1289.3.6.1, AS1289.3.1.2, AS1289.3.2.1, AS1289.3.4.1, AS1289.2.1.1, AS 1289.3.3.1
Sample Number	10599/S/19333
Sampling Method	Tested as Received
Date Sampled	8/09/2014
Sampled By	Client Sampled
Date Tested	8/09/2014
Att. Drying Method	Oven Dried
Atterberg Preparation	Dry Sieved
Material Source	CLIENT
Material Type	Clay Fill
Material Description	-

AS Sieve (mm)	Specification Minimum	Percent Passing (%)	Specification Maximum
19.0		100	
16.0		100	
13.2		100	
9.5		100	
6.7		100	
4.75		100	
2.36		99	
1.18		99	
0.600		98	
0.425		97	
0.300		96	
0.150		92	
0.075		90	



Test Result	Specification Minimum	Result	Specification Maximum	Test Result	Specification Minimum	Result	Specification Maximum
Liquid Limit (%)		71		0.075/0.425 Fines Ratio		0.93	
Plastic Limit (%)		23		PI x 0.425 Ratio (%)		4656.0	
Plastic Index (%)		48		LS x 0.425 Ratio (%)		1891.5	
Linear Shrinkage (%)		19.5		Linear Shrinkage Defects	curl		

Remarks

 The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025	 Approved Signatory: Nathan Lyne Form ID: W85Rep Rev 1
---	---


Appendix 2a

Landfill Cell Base Moisture Density and Atterberg Limit Reports

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 1/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION			
Sample Number :	WS17-8		
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Sampled By :	Ernie Taylor		
Date Sampled :	24/01/2017		
Date Tested :	25/01/2017		
Material Type :	Clayey Sand		
Material Source :	Existing		
Remarks :			
Maximum Size (mm) :	19.0	Maximum Dry Density (t/m) :	1.864
Oversize Dry (%) :	0.0	Optimum Moisture Content (%) :	12.4
Oversize Density (t/m³) :	0.0		



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218



Dean Maloney - Technical Manager
A.B.N 74465386381
141 Gidyea Street, BARCALDINE Q 4725
Phone: (07) 4651 2934
Mobile: 0428 790 309
Email: westestmaterialtesting@hotmail.com

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 1/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-8			
Test Number :	1			
Date Sampled :	24/01/2017			
Date Tested :	7/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (1) 0.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.65			
Liquid Limit (%) :	24.6			
Plastic Limit (%) :	5.2			
Plasticity Index (%) :	19.4			
Linear Shrinkage (%) :	2.4			

SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	-			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


Dean Maloney - Technical Manager
NATA Accreditation Number :
19218

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 2/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	


SAMPLE LOCATION			
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Sampled By :	Ernie Taylor		
Date Sampled :	24/01/2017		
Date Tested :	25/01/2017		
Material Type :	Clayey Sand		
Material Source :	Existing		
Remarks :			
Maximum Size (mm) :	19.0	Maximum Dry Density (t/m ³) :	1.92
Oversize Dry (%) :	0.0	Optimum Moisture Content (%) :	11.9
Oversize Density (t/m ³) :	0.0		

Moisture Density Relationship Graph



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 2/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-9			
Test Number :	2			
Date Sampled :	24/01/2017			
Date Tested :	8/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (1) 1.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.86			
Liquid Limit (%) :	27.0			
Plastic Limit (%) :	7.8			
Plasticity Index (%) :	19.2			
Linear Shrinkage (%) :	3.6			


SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	-			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY




Dean Maloney - Technical Manager
 NATA Accreditation Number :
 19218

Document Code RF26-7

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 3/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION			
Sample Number :	WS17-10		
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Sampled By :	Ernie Taylor		
Date Sampled :	24/01/2017		
Date Tested :	24/01/2017		
Material Type :	Clayey Sand		
Material Source :	Existing		
Remarks :			
Maximum Size (mm) :	19.0	Maximum Dry Density (t/m ³) :	1.866
Oversize Dry (%) :	0.0	Optimum Moisture Content (%) :	12.3
Oversize Density (t/m ³) :	0.0	Moisture Method :	Q102A



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 3/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-10			
Test Number :	3			
Date Sampled :	24/01/2017			
Date Tested :	8/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (2) 0.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.73			
Liquid Limit (%) :	25.8			
Plastic Limit (%) :	4.6			
Plasticity Index (%) :	21.2			
Linear Shrinkage (%) :	3.4			

SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	-			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY



 Dean Maloney - Technical Manager
 NATA Accreditation Number :
 19218

Dean Maloney - Technical Manager
 A.B.N 74465386381
 141 Gidyea Street, BARCALDINE Q 4725
 Phone: (07) 4651 2934
 Mobile: 0428 790 309
 Email: westestmaterialtesting@hotmail.com

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 4/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION			
Location (2) 1.5 M Depth			
Maximum Dry Density (t/m ³) :			
Optimum Moisture Content (%) :			
Maximum Size (mm) :	19.0	1.904	
Oversize Dry (%) :	0.0	11.7	
Oversize Density (t/m ³) :	0.0		



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218



Dean Maloney - Technical Manager

A.B.N 74465386381

141 Gidyea Street, BARCALDINE Q. 4725

Phone: (07) 4651 2934

Mobile: 0428 790 309

Email: westestmaterialtesting@hotmail.com

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 4/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine		

Page 1 of 1

Sample Number :	WS17-11			
Test Number :	4			
Date Sampled :	24/01/2017			
Date Tested :	9/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (2) 1.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.82			
Liquid Limit (%) :	27.2			
Plastic Limit (%) :	5.4			
Plasticity Index (%) :	21.8			
Linear Shrinkage (%) :	3.2			

SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	-			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY

Dean Maloney - Technical Manager

NATA Accreditation Number :

19218

Document Code RF26-7

Dean Maloney - Technical Manager

A.B.N 74465386381

141 Gidyea Street, BARCALDINE Q. 4725

Phone: (07) 4651 2934

Mobile: 0428 790 309


Email: westestmaterialtesting@hotmail.com

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 5/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION				
Sample Number :	WS17-12	Location (3) 0.5 M Depth		
Sampling Method :	AS1289.1.2.1 CL 6.5.4	Test Number :	5	
Sampled By :	Ernie Taylor	Lot Number :	N/A	
Date Sampled :	24/01/2017	Moisture Method :	Q102A	
Date Tested :	25/01/2017			
Material Type :	Clayey Sand	Maximum Dry Density (t/m) : 1.915		
Material Source :	Existing	Optimum Moisture Content (%) : 11.3		
Remarks :				
Maximum Size (mm) :	19.0			
Oversize Dry (%) :	0.0			
Oversize Density (t/m³) :	0.0			

Moisture Density Relationship Graph



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY



Dean Maloney - Technical Manager
NATA Accreditation Number
19218

Dean Maloney - Technical Manager

A.B.N 74465386381

141 Gidyea Street, BARCALDINE Q. 4725

Phone: (07) 4651 2934

Mobile: 0428 790 309

Email: westestmaterialtesting@hotmail.com

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 8/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-12			
Test Number :	5			
Date Sampled :	24/01/2017			
Date Tested :	9/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (3) 0.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.88			
Liquid Limit (%) :	22.0			
Plastic Limit (%) :	2.8			
Plasticity Index (%) :	19.2			
Linear Shrinkage (%) :	2.8			
SPECIFICATION DETAILS				
Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	..			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY




Dean Maloney - Technical Manager
NATA Accreditation Number :
19218

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 6/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION	
Location (3) 1.5 M Depth	
Maximum Dry Density (t/m) : 1.882	
Optimum Moisture Content (%) : 12.8	
Maximum Size (mm) :	19.0
Oversize Dry (%) :	0.0
Oversize Density (t/m³) :	0.0

Moisture Density Relationship Graph



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 5/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-13		
Test Number :	6		
Date Sampled :	24/01/2017		
Date Tested :	9/02/2017		
Sampled By :	Ernie Taylor		
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Material Source :	Existing		
Material Type :	Clayey Sand		
Sample Location :	Location (3) 1.5 M Depth		
Lot Number :	N/A		
Moisture Method :	Q102A		
Sample History :	Oven Dried		
Sample Preparation :	Dry		
Notes :	No Cracking or Crumbling		
Mould Length (mm) :	149.66		
Liquid Limit (%) :	25.4		
Plastic Limit (%) :	6.4		
Plasticity Index (%) :	19.0		
Linear Shrinkage (%) :	2.6		
SPECIFICATION DETAILS			
Specification Number :	Base WQ35 Alternative 2		
Liquid Limit - Max :	0		
Plasticity Index - Max :	0		
Linear Shrinkage - Max :	4.5		
Remarks :	-		



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY




Dean Maloney - Technical Manager
 NATA Accreditation Number :
 19218

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 7/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION			
Sample Number :	WS17-14		
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Sampled By :	Ernie Taylor		
Date Sampled :	24/01/2017		
Date Tested :	25/01/2017		
Material Type :	Clayey Sand		
Material Source :	Existing		
Remarks :			
Maximum Size (mm) :	19.0	Maximum Dry Density (t/m) :	1.891
Oversize Dry (%) :	0.0	Optimum Moisture Content (%) :	11.7
Oversize Density (t/m³) :	0.0		



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY



Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218

Dean Maloney - Technical Manager
 A.B.N 74465386381
 141 Gidyea Street, BARCALDINE Q 4725
 Phone: (07) 4651 2934
 Mobile: 0428 790 309
 Email: westestmaterialtesting@hotmail.com

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 6/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-14			
Test Number :	7			
Date Sampled :	24/01/2017			
Date Tested :	10/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (4) 0.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.51			
Liquid Limit (%) :	20.4			
Plastic Limit (%) :	13.0			
Plasticity Index (%) :	7.4			
Linear Shrinkage (%) :	3.8			

SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2		
Liquid Limit - Max :	0		
Plasticity Index - Max :	0		
Linear Shrinkage - Max :	4.5		
Remarks :	-		



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY



 Dean Maloney - Technical Manager
 NATA Accreditation Number :
 19218

Moisture Density Relationship Report

Client :	Barcaldine Regional Council	Report Number:	WT-1208 - 8/1
Address :	Ash Street Barcaldine QLD 4725	Report Date :	30/01/2017
Project Name :	Barcaldine Land Fill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q142A
Location:	Barcaldine New Dump , Barcaldine	Page 1 of 1	

SAMPLE LOCATION			
Sample Number :	WS17-15		
Sampling Method :	AS1289.1.2.1 CL 6.5.4		
Sampled By :	Ernie Taylor		
Date Sampled :	24/01/2017		
Date Tested :	25/01/2017		
Material Type :	Clayey Sand		
Material Source :	Existing		
Remarks :			
Maximum Size (mm) :	19.0	Maximum Dry Density (t/m) :	1.88
Oversize Dry (%) :	0.0	Optimum Moisture Content (%) :	12
Oversize Density (t/m³) :	0.0	Moisture Method :	Q102A

Moisture Density Relationship Graph



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number
 19218

Atterberg Limits Report

Client :	Barcaldine Regional Council	Report Number:	WT-1214 - 7/1
Address :	Ash Street Barcaldine QLD 4725, Barcaldine	Report Date :	13/02/2017
Project Name :	Barcaldine Landfill Site	Order Number :	N/A
Project Number :	WT-1214	Test Method :	Q104D,Q105,Q106
Location:	New Landfill Site , Barcaldine	Page 1 of 1	

Sample Number :	WS17-15			
Test Number :	8			
Date Sampled :	24/01/2017			
Date Tested :	10/02/2017			
Sampled By :	Ernie Taylor			
Sampling Method :	AS1289.1.2.1 CL 6.5.4			
Material Source :	Existing			
Material Type :	Clayey Sand			
Sample Location :	Location (4) 1.5 M Depth			
Lot Number :	N/A			
Moisture Method :	Q102A			
Sample History :	Oven Dried			
Sample Preparation :	Dry			
Notes :	No Cracking or Crumbling			
Mould Length (mm) :	149.64			
Liquid Limit (%) :	21.6			
Plastic Limit (%) :	12.4			
Plasticity Index (%) :	9.2			
Linear Shrinkage (%) :	3.2			

SPECIFICATION DETAILS

Specification Number :	Base WQ35 Alternative 2			
Liquid Limit - Max :	0			
Plasticity Index - Max :	0			
Linear Shrinkage - Max :	4.5			
Remarks :	-			



Accredited For Compliance With ISO/IEC 17025

APPROVED SIGNATORY


 Dean Maloney - Technical Manager
 NATA Accreditation Number :
 19218

Appendix 2b

Landfill Cell Base Permeability Reports

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33905-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	16/02/2017 Page 1 of 1

Test Procedures:	AS1289.6.7.2		
Sample Number	2128/S/57218		
Sampling Method	Tested As Received	Location	WS17-8
Date Sampled	21/01/2017		Location 1
Sampled By	Client Sampled		0.5m
Date Tested	6/02/2017	Material Type	In situ
Material Source	Existing		

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m ³)	1.86400	Optimum Moisture Content (%)	12.4
Dry Density of Sample (t/m ³)	1.801	Moisture at Compaction (%)	12.8
Achieved Dry Density Ratio (%)	96.6	Achieved Moisture Ratio (%)	103.2
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	17.7	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	3E-009 m/s (3E-007 cm/s)
---	-------------------------------------

Remarks

 The results of the tests, calibrations and/or measurements included in this document are traceable to Australian national standards. Accredited for compliance with ISO/IEC 17025 Accreditation Number: 1986 Corporate Site Number: 2128	 Approved Signatory: Lee Draper Form ID: W49Rep Rev1
--	---

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33906-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	16/02/2017 Page 1 of 1

Test Procedures:	AS1289.6.7.2		
Sample Number	2128/S/57219		
Sampling Method	Tested As Received	Location	WS17-9
Date Sampled	21/01/2017		Location 1
Sampled By	Client Sampled		1.5m
Date Tested	6/02/2017	Material Type	In situ
Material Source	Existing		

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m ³)	1.92000	Optimum Moisture Content (%)	11.9
Dry Density of Sample (t/m ³)	1.866	Moisture at Compaction (%)	11.7
Achieved Dry Density Ratio (%)	97.2	Achieved Moisture Ratio (%)	98.3
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	14.8	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	9E-010 m/s (9E-008 cm/s)
--	-----------------------------

Remarks

<p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 2128</p>	<p>Approved Signatory: Lee Draper Form ID: W49Rep Rev1</p>
--	--

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33907-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	16/02/2017 Page 1 of 1

Test Procedures:	AS1289.6.7.2		
Sample Number	2128/S/57220	Sample Location	
Sampling Method	Tested As Received	Location	WS17-10
Date Sampled	21/01/2017		Location 2
Sampled By	Client Sampled		0.5m
Date Tested	6/02/2017	Material Type	In situ
Material Source	Existing		

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m ³)	1.86600	Optimum Moisture Content (%)	12.3
Dry Density of Sample (t/m ³)	1.809	Moisture at Compaction (%)	12.4
Achieved Dry Density Ratio (%)	96.9	Achieved Moisture Ratio (%)	100.8
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	16.7	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	9E-010 m/s (9E-008 cm/s)
---	-------------------------------------

Remarks

 <p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 2128</p>	 Approved Signatory: Lee Draper Form ID: W49Rep Rev1
--	---

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33908-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	16/02/2017
			Page 1 of 1

Test Procedures: AS1289.6.7.2	
Sample Number	2128/S/57221
Sampling Method	Tested As Received
Date Sampled	21/01/2017
Sampled By	Client Sampled
Date Tested	6/02/2017
Material Source	Existing
	Sample Location
	Location WS17-11
	Location 2
	1.5m
	Material Type In-situ

Soil Description:			
Retained on 10.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m³)	1.90400	Optimum Moisture Content (%)	11.7
Dry Density of Sample (t/m³)	1.847	Moisture at Compaction (%)	11.7
Achieved Dry Density Ratio (%)	97.0	Achieved Moisture Ratio (%)	100.0
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	14.9	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	6E-009 m/s (6E-007 cm/s)
---	-------------------------------------

Remarks

 The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025 Accreditation Number: 1986 Corporate Site Number: 2128	 Approved Signatory: Lee Draper Form ID: W49Rep Rev1
--	---

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33979-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	22/02/2017 Page 1 of 1

Test Procedures:	AS1289.8.7.2		
Sample Number	2128/S/57222		
Sampling Method	Tested As Received	Location	WS17-12
Date Sampled	21/01/2017		Location 3
Sampled By	Client Sampled		0.5m
Date Tested	6/02/2017	Material Type	In situ
Material Source	Existing		

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m³)	1.91500	Optimum Moisture Content (%)	11.3
Dry Density of Sample (t/m³)	1.858	Moisture at Compaction (%)	11.3
Achieved Dry Density Ratio (%)	97.0	Achieved Moisture Ratio (%)	100.0
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	13.7	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	2E-009 m/s (2E-007 cm/s)
--	-----------------------------

Remarks

<p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 2128</p>	<p>Approved Signatory: Lee Draper Form ID: W49Rep Rev1</p>
--	--

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33996-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	23/02/2017 Page 1 of 1

Test Procedures: AS1289.6.7.2	
Sample Number	2128/S/57223
Sampling Method	Tested As Received
Date Sampled	21/01/2017
Sampled By	Client Sampled
Date Tested	6/02/2017
Material Source	Existing
	Material Type In situ

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m ³)	1.88200	Optimum Moisture Content (%)	12.8
Dry Density of Sample (t/m ³)	1.822	Moisture at Compaction (%)	13.0
Achieved Dry Density Ratio (%)	96.8	Achieved Moisture Ratio (%)	101.6
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	15.1	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	8E-010 m/s (8E-008 cm/s)
---	-------------------------------------

Remarks

 <p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 2128</p>	 <p>Approved Signatory: Lee Draper Form ID: W49Rep Rev1</p>
--	--

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33997-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	23/02/2017 Page 1 of 1

Test Procedures:	AS1289.6.7.2
Sample Number	2128/S/57224
Sampling Method	Tested As Received
Date Sampled	21/01/2017
Sampled By	Client Sampled
Date Tested	6/02/2017
Material Source	Existing
	Sample Location
	Location WS17-14
	Location 4
	0.5m
	Material Type In-situ

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m³)	1.89100	Optimum Moisture Content (%)	11.7
Dry Density of Sample (t/m³)	1.829	Moisture at Compaction (%)	12.0
Achieved Dry Density Ratio (%)	96.7	Achieved Moisture Ratio (%)	102.6
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	14.1	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	8E-010 m/s (8E-008 cm/s)
---	-----------------------------

Remarks

<p>The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025</p> <p>Accreditation Number: 1986 Corporate Site Number: 2128</p>	<p>Approved Signatory: Lee Draper Form ID: W49Rep Rev1</p>
--	--

PERMEABILITY OF A SOIL

Client:	WESTEST MATERIALS TESTING SERVICES	Report Number:	2128/R/33998-1
Client Address:	141 Gidyea Street, Barcaldine	Project Number:	2128/P/842
Project:	General Testing	Lot Number:	
Location:	QLD	Internal Test Request:	2128/T/13849
Component:	BARCALDINE REGIONAL COUNCIL	Client Reference/s:	WT-1214 - 21/1/17
Area Description:		Report Date / Page:	23/02/2017 Page 1 of 1

Test Procedures:	AS1289.6.7.2		
Sample Number	2128/S/57225		
Sampling Method	Tested As Received	Location	WS17-15
Date Sampled	21/01/2017		Location 4
Sampled By	Client Sampled		1.5m
Date Tested	02/02/2017	Material Type	In situ
Material Source	Existing		

Soil Description:			
Retained on 19.0 mm Sieve (%)	-	Compaction Method:	Standard
Maximum Dry Density (t/m ³)	1.88000	Optimum Moisture Content (%)	12.0
Dry Density of Sample (t/m ³)	1.822	Moisture at Compaction (%)	12.1
Achieved Dry Density Ratio (%)	96.9	Achieved Moisture Ratio (%)	100.8
Surcharge Mass (kg)	5.000	Surcharge Pressure (kPa)	2.8
Moisture % After Permeability (%)	15.1	Hydraulic Gradient	

Coefficient of Permeability (Falling Head)	2E-009 m/s (2E-007 cm/s)
--	-----------------------------

Remarks

 The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025 Accreditation Number: 1986 Corporate Site Number: 2128	 Approved Signatory: Lee Draper Form ID: W49Rep Rev1
--	---